

ADHESIVES & SEALANTS FOR TRANSPORT INDUSTRIES



Permabond adhesives are specified worldwide for use in the manufacture, repair, and maintenance of airplanes, trains, buses, and automobiles- which all require adhesives for a broad range of bonding applications

In many cases, welding, brazing, and mechanical fasteners are simply not suitable. Adhesives are vital for locking nuts and bolts together to prevent vibration loosening. They also help prevent parts seizing due to corrosion, making it easy to disassemble for repair or maintenance

Permabond® Adhesives are used on the exterior panels and mirrors, under the hood and on the interior.

Typical applications include:

► **Panel bonding - Various products with no read through**

► **Gearbox & Transmission**

- FIP Gaskets for cover - no bedding in, one adhesive can make any shaped gasket
- High strength adhesives for bonding gears to shaft
- Threadlockers - to prevent vibration loosening
- Bearing fit adhesives

► **Drive Shaft & Axles**

- Driveshaft and axle bonding with high strength toughened adhesives.
- Bonding bearing into housings and yokes
- Threadlocking bolts
- Sealing hubs
- Retaining shafts and spline

► **Interior**

- Air vents
- Book shelving in bookmobiles
- Blinds in mobile medical centers
- Cable containment clips in mobile command centers
- Emergency floor lighting
- Floor panels and treads Bus Blinds
- Handrails



IDEAL FOR BONDING:

- | | | |
|----------------|------------------|-------------------|
| • ABS | • Glass | • Polyethylene* |
| • Acrylic | • Laminate | • Polystyrene |
| • Aluminum | • Leather | • PVC |
| • Carbon Fiber | • Nylon | • Rubber |
| • Composite | • Phenolic | • Steel |
| • EPDM | • Polycarbonate | • Titanium Zinc |
| • FRP/GRP | • Polypropylene* | ...and many more! |
| • Ferrite | | |

*Specific grades only

TRANSPORT INDUSTRY ADHESIVES AND SEALANTS

Example Application	Product	Features	Cure Method	Viscosity (mPa.s) cP	Gap Fill (mm) in	Handling Time	Max. Shear Strength Steel (MPa) psi
Exterior panels / skins Interior composite panelling	TA4210*	Toughened, gap filling, low shrinkage, 1:1 mix ratio, easy to apply	2-part pre-mix acrylic (cartridge and mixing nozzle system) room temperature cure	45,000	(4.0) 0.16	20-25 minutes	(25) 3600
	TA4810**			50,000	(2.0) 0.08	10-15 minutes	(28) 4000
	MS359 Series	Very flexible, low shrinkage and low read through, available in Non-sag and Self-levelling grades	1-part MS polymer, moisture cure at 4mm/24 hour	Various	(5.0) 0.2	15 min skin over time	3 (430)
	MT3821	Soft flexible, 2:1 mixable faster cure than MS359, non-slump	2-part modified epoxy	Thixotropic Paste	(5.0) 0.2	60 - 90 minutes	7 (1000)
	PT328	Resilient, non-slump	2-part urethane	5000	(5.0) 0.2	60 - 90 minutes	20 (2900)
Gasketing - engine and gearbox	MH196	High temperature resistant, can form gaskets in all shapes and sizes	Single part anaerobic, cures at room temperature in the presence of metal and in the exclusion of oxygen	2rpm: 500,000 20rpm: 100,000	(0.5) 0.02	15 minutes (on steel)	(10) 1450
Fixing bearings, shafts & splines	HM162	High strength, high temperature resistance, rapid cure	Single part anaerobic, cures at room temperature in the presence of metal and in the exclusion of oxygen	1000	(0.2) 0.008	5 minutes (on steel)	(30) 4300
Sealing pipework, heating etc	MH052	Suitable for sealing against fuel, autogas, water, oxygen	Single part anaerobic, cures at room temperature in the presence of metal and in the exclusion of oxygen	2rpm: 65,000 20rpm: 25,000	(0.5) 0.02	15 minutes (on steel)	(10) 1450
Heat exchanger sealing	ES558	Wicking to penetrate around tubes and fins, metallic appearance	Single part heat cure epoxy	200,000 -Flows like solder when heated	(0.5) 0.02	NA Cure 1 hour 150°C/300°F	(41) 6000
Bonding seat trays, side (wing) mirrors	ET515	Toughened, flexible, rapid curing, clear epoxy with high peel strength	2-part pre-mix epoxy (cartridge and mixing nozzle system), room temperature cure	17,000	(2.0) 0.08	20-30 minutes	(12) 1740
Bonding interior trim, blinds, fascia	2011	Non-drip, rapid curing, high strength surface insensitive gel	No mix, moisture cure Wcyanoacrylate	Gel	(0.5) 0.02	5-10 seconds (on plastic)	(24) 3500
Bonding interior handrails	HM165	High performance, high strength, rapid curing	Single part anaerobic, cures at room temperature in the presence of metal and in the exclusion of oxygen	2rpm: 25,000 20rpm: 10,000	(0.3) 0.012	15-20 minutes (on steel)	(26) 3800

If you can't see the exact product you are looking for, or need more in depth technical information, Permabond's technical team would be more than happy to help.

*Available Europe, Middle East, and Australia

**Available in The Americas and Asia

PERMABOND.COM

Authorized distributor stamp:



info.americas@permabond.com US 732 868 1372

info.europe@permabond.com UK +44 (0)1962 711661

info.asia@permabond.com Asia +86 21 5773 4913

The information given and the recommendations made herein are based on our experience and are believed to be accurate. No guarantee as to, or responsibility for, their accuracy can be given or accepted, however, and no statement herein is to be treated as a representation or warranty. In every case we urge and recommend that purchasers, before using any product, make their own tests to determine, to their own satisfaction, its suitability for their particular purposes under their own operating conditions. Always refer to current product technical datasheet for most recent and accurate technical information.