

Safety Data Sheet

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

1. Identification

1.1. Product identifier

Product name **Permabond ET5145A**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Adhesive**

Identified Uses	Industrial	Professional	Consumer
Use	✓	✓	-

1.3. Details of the supplier of the safety data sheet

Name **Permabond Engineering Adhesives**
Full address **Niederlasser Lohweg 18**
District and Country **40547 Düsseldorf Germany**
Tel. **+44 (0)1962 711 661**
e-mail address of the competent person responsible for the Safety Data Sheet **info.europe@permabond.com**

Supplier: **Permabond LCC**
14 Robinson Street
Pottstown, PA 19464, USA
tel 732-868-1372 OR 800-640-7599
www.permabond.com

1.4. Emergency telephone number

For urgent inquiries refer to **Medical: Poison Control Center 866-827-6282 (toll free) or 303-389-1109**
Transport: CHEMTREC 800-424-9300 (toll free) or 1-703-741-5970

2. Hazards identification

2.1. Classification of the substance or mixture

Classification and Hazard Statement
Eye irritation, category 2 Causes serious eye irritation.
Skin irritation, category 2 Causes skin irritation.
Skin sensitization, category 1 May cause an allergic skin reaction.
Hazard pictograms:



Signal words: **Warning**

Hazard statements:
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

Precautionary statements:
Prevention:
P261 Avoid breathing vapors or aerosols.
P280 Wear protective gloves / eye protection / face protection.
P264 Carefully wash the contaminated skin after use.
P272 Contaminated work clothing should not be allowed out of the workplace.
Response:

Permabond ET5145A

2. Hazards identification ... / >>

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice / attention.
P337+P313	If eye irritation persists: Get medical advice / attention.
P302+P352	In case of contact with the skin: wash abundantly with soap and water.
P362+P364	Take off contaminated clothing and wash it before reuse.
P363	Wash contaminated clothing before reuse.
Storage:	--
Disposal:	
P501	Dispose of the product according to current regulations.

2.2. Other hazards

No other hazards known.

3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification:
EPOXY RESIN (Number average MW <= 700)	30 ≤ x < 60	Eye irritation, category 2 H319, Skin irritation, category 2 H315, Skin sensitization, category 1 H317
EC 216-823-5		
CAS 1675-54-3		
REACH Reg. 01-2119456619-26-XXXX		
GLYCEROL PROPOXY TRIACRYLATE	5 ≤ x < 10	Eye irritation, category 2 H319, Skin sensitization, category 1 H317
EC 500-114-5		
CAS 52408-84-1		
REACH Reg. 01-2119487948-12-XXXX		

* There is a batch to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.
SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.
INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.
INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT
The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.
UNSUITABLE EXTINGUISHING EQUIPMENT
None in particular.

5. Fire-fighting measures ... / >>**5.2. Special hazards arising from the substance or mixture**

HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE

Avoid breathing combustion products, carbon monoxide (CO), carbon dioxide (CO₂), and nitric oxides (NO_x).

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage**7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection**8.1. Control parameters**

Information not available

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves.

8. Exposure controls/personal protection ... / >>

The following should be considered when choosing work glove material (OSHA 29 CFR 1910.138): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	viscous liquid	
Colour	white	
Odour	mild	
Odour threshold	not available	
pH	not available	Reason for missing data: substance/mixture is non-soluble (in water)
Melting point / freezing point	not available	
Initial boiling point	not available	
Boiling range	not available	
Flash point	> 100 °C (212 °F)	
Evaporation rate	not available	
Flammability	not available	
Lower inflammability limit	not available	
Upper inflammability limit	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Vapour pressure	not available	
Vapour density	not available	
Relative density	1.3	
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
Viscosity	not available	
Explosive properties	not available	
Oxidising properties	not available	

9.2. Other information

Information not available

10. Stability and reactivity

10.1. Reactivity

The following materials may react with the product: Strong oxidizing agents, Reducing agents, strong acids and bases.

10.2. Chemical stability

10. Stability and reactivity ... / >>

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Stable under normal conditions of storage and use.
Protect from direct sunlight.
Avoid contact with acids and oxidizing agents.

10.5. Incompatible materials

See the reactivity section.

10.6. Hazardous decomposition products

By thermal decomposition, carbon monoxide, carbon dioxide and other unidentified organic compounds.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effectsMetabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

EPOXY RESIN (Number average MW <= 700)

LD50 (Oral): > 2000 mg/kg

LD50 (Dermal): > 2000 mg/kg

GLYCEROL PROPOXY TRIACRYLATE

LD50 (Oral): > 2000 mg/kg

LD50 (Dermal): > 2000 mg/kg

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

11. Toxicological information ... / >>

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Carcinogenicity Assessment:

1675-54-3 EPOXY RESIN (Number average MW <= 700)
IARC:3

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

12.1. Toxicity

EPOXY RESIN (Number average MW <= 700)

LC50 - for Fish	2 mg/l/96h
EC50 - for Crustacea	1.8 mg/l/48h
EC50 - for Algae / Aquatic Plants	11 mg/l/72h
Chronic NOEC for Crustacea	0.3 mg/l
Chronic NOEC for Algae / Aquatic Plants	4.2 mg/l

12.2. Persistence and degradability

EPOXY RESIN (Number average MW <= 700)
NOT rapidly degradable

12.3. Bioaccumulative potential

EPOXY RESIN (Number average MW <= 700)

BCF	31
-----	----

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12. Ecological information ... / >>

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to ADR provisions.

IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to IMDG Code provisions.

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to IATA dangerous goods regulations.

14.2. UN proper shipping name

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW ≤ 700))
IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW ≤ 700))
IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW ≤ 700))

14.3. Transport hazard class(es)

ADR / RID: Class: 9 Label: 9



IMDG: Class: 9 Label: 9



IATA: Class: 9 Label: 9



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: Environmentally Hazardous



Permabond ET5145A**14. Transport information ... / >>****14.6. Special precautions for user**

ADR / RID:	HIN - Kemler: 90	Limited Quantities: 5 L	Tunnel restriction code: (-)
IMDG:	Special provision: -	Limited Quantities: 5 L	
IATA:	EMS: F-A, S-F	Maximum quantity: 450 L	Packaging instructions: 964
	Cargo:	Maximum quantity: 450 L	Packaging instructions: 964
	Passengers:	Maximum quantity: 450 L	
	Special provision:	A97, A158, A197, A215	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**U.S. Federal RegulationsTSCA:

All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory or are exempt from the listing / notification requirements.

Clean Air Act Section 112(b):

No component(s) listed.

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:313 Category Code:

No component(s) listed.

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

No component(s) listed.

EPCRA 313 TRI:

No component(s) listed.

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

15. Regulatory information ... / >>

State Regulations

Massachussetts:

No component(s) listed.

Minnesota:

No component(s) listed.

New Jersey:

No component(s) listed.

New York:

No component(s) listed.

Pennsylvania:

No component(s) listed.

California:

No component(s) listed.

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAA 112 @ RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112@)
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: Regulation (EC) 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REACH: Regulation (EC) 1907/2006

16. Other information ... / >>

- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112© of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.